

C29



Characteristics

| | |
|--|---|
| Temperature Range | +10/-10 °C |
| Capacity | 29 lt (1,02 cu ft) |
| External Dimensions (W x D x H) | cm 53 X 34,5 X 39 <i>Internal dimensions (W x D x H) cm 27,5 x 26 x 30,5 (+ additional compartment 15,5 x 26 x 11); Weight kg 16</i> |
| Structure and Insulation | Atoxic plastic material int./est., thickness 40 mm |
| Door | Nr 1 blind lid |
| Key Lock | |
| Internal equipment | Nr 1 open wire basket dim. cm. 28 x 25 x 25 (W x D x H) Nr.2 cables: for 12/24V and for 110/240V |
| Controller | Digital electronic thermostat |
| Alarms | Acoustic and Visual for temperature deviations |
| Refrigeration Type | Static |
| Defrost | Manual |

Technical data

| | |
|---------------------------|--|
| Details | <ul style="list-style-type: none"> • Refrigerant type: R600a CFC free • Mains Voltage 12V/24V; 110V/240V/50Hz-60Hz • Nominal consumption 12 Vcc: 2,58 A • Nominal power consumption: 31 W • Ambient Temperature: +10/+32 °C; humidity 60% |
| In accordance with | 2014/30/CE, 2014/35/CE and following modifications |
| Package | Strong Cardboard on wooden pallet <i>Dim. cm.64x42x56; Kg.23</i> <ul style="list-style-type: none"> • Wooden crate on wooden pallet available: dim. cm.66x48x61; Kg.36 |

Accessories

Graphic Chart Recorder

Datalogger

C.F. di Ciro Fiocchetti & C. s.n.c.
 Via Panagulis, 48 - 42045 Luzzara (RE) Italy
 Tel. +39 0522 976232- Fax +39 0522 976028
 info@fiocchetti.it - www.fiocchetti.it
 P.I.00934960352
 Registro A.E.E. IT8020000002833

C41



Characteristics

| | |
|--|---|
| Temperature Range | +10 / -10 °C |
| Capacity | 41 lt (1,45 cu ft) |
| External Dimensions (W x D x H) | cm 60 x 37 x 40 |
| | <i>Internal Dimensions (W x D x H) cm 37x 28,5 x 30 (+ additional compartment 15 x 28,5 x 12,5); Weight kg 17</i> |
| Structure and Insulation | Atoxic plastic material int./est., thickness 40 mm |
| Door | Nr 1 blind lid |
| Key Lock | |
| Internal equipment | Nr 1 open wire basket dim. cm. 28 x 25 x 25 (W x D x H) Nr.2 cables: for 12/24V and for 110/240V |
| Controller | Digital electronic thermostat |
| Alarms | Acoustic and Visual for temperature deviations |
| Refrigeration Type | Static |
| Defrost | manual |

Technical data

| | |
|---------------------------|---|
| Details | <ul style="list-style-type: none"> • Refrigerant type: R600a CFC free • Mains Voltage 12V/24V; 110V/240V/50Hz-60Hz • Nominal consumption 12 Vcc: 2,58 A • Nominal power consumption: 31 W • Ambient Temperature: +10/+32 °C; humidity 60% • Connectors: 2 Sockets (1 for 12/24V and 1 for 230V) |
| In accordance with | 2014/30/CE, 2014/35/CE and following modifications |
| Package | Strong Cardboard on wooden pallet |
| | <i>Dim. cm.64x42x56; Kg.23</i> |
| | • <i>Wooden crate on wooden pallet available: dim. cm.75x50x62; Kg.36</i> |

Accessories

Graphic Chart Recorder

Datalogger

C.F. di Ciro Fiocchetti & C. s.n.c.

Via Panagulis, 48 - 42045 Luzzara (RE) Italy
 Tel. +39 0522 976232- Fax +39 0522 976028
 info@fiocchetti.it - www.fiocchetti.it
 P.I.00934960352
 Registro A.E.E. IT8020000002833

C65



Characteristics

| | |
|--|--|
| Temperature Range | +10 / -20 °C |
| Capacity | 65 lt (2,30 cu ft) |
| External Dimensions (W x D x H) | cm 70 x 44 x 47 |
| | <i>Internal Dimensions (W x D x H) cm 47 x 37,5 x 35 (+ additional compartment 15 x 37,5 x 17); Weight kg 24</i> |
| Structure and Insulation | Atoxic plastic material int./est., thickness 40 mm |
| Door | Nr 1 blind lid |
| Key Lock | |
| Internal equipment | Nr 1 open wire basket dim. cm. 46 x 36 x 32 (W x D x H) Nr.2 cables: for 12/24V and for 110/240V |
| Controller | Digital electronic thermostat |
| Alarms | Acoustic and Visual for temperature deviations |
| Refrigeration Type | Static |
| Defrost | manual |

Technical data

| | |
|---------------------------|---|
| Details | <ul style="list-style-type: none"> • Refrigerant type: R600a CFC free • Mains Voltage 12V/24V; 110V/240V/50Hz-60Hz • Nominal consumption 12 Vcc: 3,68 A • Nominal power consumption: 45 W • Ambient Temperature: +10/+32 °C; humidity 60% • Connectors: 2 Sockets (1 for 12/24V and 1 for 230V) |
| In accordance with | 2014/30/CE, 2014/35/CE and following modifications |
| Package | Strong Cardboard on wooden pallet |
| | <i>Dim. cm.80x60x63; Kg.32</i> |
| | • <i>Wooden crate on wooden pallet available: dim. cm.85x57x69; Kg.45</i> |

Accessories

Graphic Chart Recorder

Datalogger

C.F. di Ciro Fiocchetti & C. s.n.c.

Via Panagulis, 48 - 42045 Luzzara (RE) Italy
 Tel. +39 0522 976232- Fax +39 0522 976028
 info@fiocchetti.it - www.fiocchetti.it
 P.I.00934960352
 Registro A.E.E. IT8020000002833

C65T



Characteristics

| | |
|--|---|
| Temperature Range | +30/-20°C <i>Setpoint +22°C</i> |
| Capacity | 65 lt (2,30 cu ft) |
| External Dimensions (W x D x H) | cm 70 x 44 x 47 <i>Internal Dimensions (W x D x H) cm 47 x 37,5 x 35 (+ additional compartment 15 x 37,5 x 17); Weight kg 24</i> |
| Structure and Insulation | Atoxic plastic material int./est., thickness 40 mm |
| Door | Nr 1 blind lid |
| Key Lock | |
| Internal equipment | Nr 1 open wire basket dim. cm. 46 x 36 x 32 (W x D x H) Nr.1 cable 12V |
| Controller | Digital electronic thermostat |
| Alarms | Acoustic and Visual for temperature deviations |
| Refrigeration Type | Static |
| Defrost | Manual |

Technical data

Details

- Refrigerant type: R134a CFC free
- Mains Voltage 12V;
- Nominal consumption 12 Vcc: 3,68 A
- Nominal power consumption: 45 W
- Ambient Temperature: +10/+32 °C; humidity 60%
- Connectors: Socket for 12/24V

In accordance with 2014/30/CE, 2014/35/CE and following modifications

Accessories

Trasformer 230V

Graphic Chart Recorder

Datalogger

C.F. di Ciro Fiocchetti & C. s.n.c.

Via Panagulis, 48 - 42045 Luzzara (RE) Italy
 Tel. +39 0522 976232- Fax +39 0522 976028
 info@fiocchetti.it - www.fiocchetti.it
 P.I.00934960352
 Registro A.E.E. IT8020000002833